


HGP-1.5A

- Displacement : 0.8~8 cc/rev
- Max. Pressure : 350 kgf/cm²
(4900psi)



SCHEMATIC SYMBOL



ORDER CODES

HGP-1.5A - **F** - **2** - **R** - **Y**

1
 2
 3
 4
 5

1 Model Name	HGP-1.5A	
2 Mounting	F	flange type
3 Delivery Capacity	08, 1, 12, 16, 2, 25, 3, 4, 5, 65, 8	
4 Rotation Direction	R	clockwise
	L	counter - clockwise
5 Shaft Type	Y	spline shaft

SPECIFICATIONS

Model	Accurate Displacement Capacity (cc/rev)	Operational Pressure (kgf/cm ²)	Max. Pressure (kgf/cm ²)	Speed (r.p.m.)			Weight (kg)
				Rate	Max.	Min.	
HGP-1.5A-08	0.8	300	350	1800	5000	1000	0.89
HGP-1.5A-1	1	300	350	1800	5000	800	0.91
HGP-1.5A-12	1.2	300	350	1800	5000	800	0.92
HGP-1.5A-16	1.6	300	350	1800	5000	800	0.93
HGP-1.5A-2	2	300	350	1800	4000	800	0.94
HGP-1.5A-25	2.5	300	350	1800	4000	800	0.95
HGP-1.5A-3	3.1	300	350	1800	4000	700	0.97
HGP-1.5A-4	4	300	350	1800	4000	600	1.0
HGP-1.5A-5	5	250	300	1800	4000	500	1.04
HGP-1.5A-65	6.3	250	300	1800	3200	500	1.14
HGP-1.5A-8	8	210	250	1800	2400	500	1.17

DIMENSIONS (unit : mm)
